

Excellence



EXCELLENCE is a high-performance emergency luminaire designed for indoor environments, combining IP42 protection with IK04 impact resistance. Engineered for versatility, it supports wall installation or recessed mounting with the dedicated accessory, ensuring seamless integration into any space.


Emergency lighting

Versions	Excellence	Pictogram accessories
Diffusers	Area Evacuation Wall-mounted	
Control options		
Finish	RAL9016	RAL9005
Customization	Finish Remote control	
	 	

 SPECIFICATIONS SUBJECT TO UPDATES OR MODIFICATIONS.



Emergency luminaire



Surface

Lumen output	110 - 330 lm
Duration	1/3 h
Operating modes	Maintained / Non-maintained
CCT	5700
Versions	Standard Autotest DALI Wireless Central Battery System
Battery	Ni-MH Ni-Cd LiFePO4
Charging	Max. 24 h
IP	42
IK	04
Power supply	230 Vac / 24 Vdc
Mounting options	Surface Recessed Wall-mounted
Standards	EN IEC 60598-2-22 EN IEC 60598-1



Emergency lighting accessories

Pictograms



Type PAM 330 × 155 mm

Maximum viewing distance
(according to EN ISO 1838 for internally illuminated signs)

20 m



Type PEM 355 × 150 mm

Maximum viewing distance
(according to EN ISO 1838 for internally illuminated signs)

30 m



Normagrup Technology Headquarters
Parque Tecnológico de Asturias. C/Ablanal, 1
33428 Llanera (Asturias), Spain

Normagrup UK
Normagrup Netherlands
Normagrup France

Specifications subject to updates or modifications.



normagrup.com

