


Lissa




LISSA is an exit signage luminaire made of extruded aluminium with a methacrylate panel. It offers high visibility (up to 50 m) and supports pictograms for evacuation or fire-fighting.

Exit signs

Versions	Lissa	 VIEWING DISTANCE = 50 m
Diffusers	Multitiled	
Control options		
Finish	RAL9016 RAL7001 RAL9005	
Customization	Finish	 



Exit signs



Surface

Duration	1/3 h
Operating modes	Maintained / Non-maintained
CCT	5700
Versions	Standard Autotest DALI Central Battery System
Battery	Ni-Cd Ni-MH LiFePO4
Charging	Max. 24 h
IP	20
IK	04
Power supply	230 Vac / 24 Vdc
Mounting options	Surface Suspended Wall-mounted paralell Wall-mounted perpendicular* Track-mounted*
Standards	EN IEC 60598-2-22 EN IEC 60598-1
Viewing distance	50 m
EN ISO 1838	10 m
CTE	



* Using an accessory

Each fitting includes:

- + 1 fitting
- + 1 diffuser blade
- + 4 pictograms (2 left, 1 down, 1 white)

Accessories

- **Black** Add "N" to the reference.
- **Grey** Add "G" to the reference.

Pictograms	Type PLN	Non adhesive pictogram 500 × 250 mm. <i>References according to table below</i>			
	Type PLN 500 × 250 mm	REF. PLN-A	REF. PLN-A	REF. PLN-SD	REF. PLN-SU
					
		Maximum viewing distance (according to EN ISO 1838 for internally illuminated signs)			
		50 m			
		REF. PLN-BIE	REF. PLN-EXT	REF. PLN-PUL	
					
		Maximum viewing distance (according to EN ISO 1838 for internally illuminated signs)			
		10 m			

 PLEASE CHECK FOR OTHER PICTOGRAMS

Normagrup Technology Headquarters
Parque Tecnológico de Asturias. C/Ablanal, 1
33428 Llanera (Asturias), Spain

Normagrup UK
Normagrup Netherlands
Normagrup France

Specifications subject to updates or modifications.



normagrup.com

